

T568A WIRING

- Pin 1 White/Green
- Pin 2 Green
- Pin 3 White/Blue
- Pin 4 Blue
- Pin 5 White/Orange
- Pin 6 Orange
- Pin 7 White/Brown
- Pin 8 Brown

T568B WIRING


- Pin 1 White/Orange
- Pin 2 Orange
- Pin 3 White/Blue
- Pin 4 Blue
- Pin 5 White/Green
- Pin 6 Green
- Pin 7 White/Brown
- Pin 8 Brown

SPECIFICATION



1. Mount Box: Up & Bottom Case, ABS UL 94HB rated.
2. RJ45 JACK---Body: PBT 94V-0 rated, Black color.
Contact: Phosphor Bronze, 50u" gold plated over Nickel plated in contact area
3. Connector: New 110D Connector---Body: PC UL 94V-2, white color.
Tin-lead over nickel in solder area.
Contact: Phosphor Bronze with Tin plated.
4. P.C.Board: FR4 1.6 m/m Double side.

Remark: Item No: JE309-USX
X=D dual port.
S single port.


Note: TOL ± 0.1m/m



RJ45 Right Angle



5 position
New version



4 position
New version

UNIT	M/M	DSGN	MAGIC	08.FEB.2001	ITEM NO:	JE309CE-USD/XX
SCALE	1/1	CHK			APPR	Surfaced Mounted Box, Unshielded 2port
DWG NO:	JE309CEUSD	JYH ENG IND CO., LTD				