

Date: 06/06/2008

NO.:

<b>Customer</b>	Sweden Direktronik	<b>RoHS</b>	Yes
<b>Product Name</b>	Designated Power Distribution Unit for Cabinet	<b>Customer's Code</b>	
<b>Part Number</b>	16-8138	<b>Picture Code</b>	
<b>No.</b>	<b>Item</b>	<b>Detailed Description</b>	
1	Product Series		
2	Socket Type	Double IEC320 C13 Socket[13];	
3	Socket Quantity	26	
4	Power Input	Left end single input	
5	Bracket Install	Inverse installation	
6	Cable with plug	IEC60309 plug (32A 3P+N+E)	
7	Control Function	No controlling function	
8	Protection Function	No protecting function	
9	Case	Black	
10	Cable Specification	5 x 6.0 mm <sup>2</sup> x 2M	
11	Product Size	L x W x H = 888.5 x 68 x 44.4 mm	
12	Mounting Length	862 mm	
13	Case Length	835.5 mm	
14	Fittings	2pcs $\phi$ 6x16mm cross bolt, 2pcs M6 float nut	
15	Product Label	Product Name	Designated Power Distribution Unit for Cabinet
		Specification Model	16-8138
		Rating voltage	380VAC input/ 250VAC output
		Rating Current	3x32A
		Max. Current	
		Max. Power	
		Safety Authentication	CE
		Logo	RoHS
	Producer		
<b>No.</b>	<b>Add-In</b>		
1	Socket assemble	No	
2	Interior Connection Wire	2.5 mm <sup>2</sup>	
3	Interior Connection Style	Group connection	
4	Fix the Cable	Cable clamp	
5	Module Assemble ( form left to right )	Please see the following picture	
6	Others	No	
<b>Made by:</b> Peter		<b>Customer confirm:</b>	<b>Check:</b>
			<b>Authorize:</b>

**This technology specification is for: design product for customer and confirm customer's requirements, and is also the basic gist for arranging production.**

Preview



IEC60309 plug (32A 3P+N+E)

**DIREKTRONIK**

Direktronik AB tel. 08-52 400 700 www.direktronik.se

Date: 06/06/2008

NO.:

DIMENSION AND TOLERANCES (Unit: mm)			Direktronik AB	
Length: 888.5	Mounting length: 862		Customer	Sweden Direktronik
Width: 68	Case length: 835.5		Product name	Designated Power Distribution Unit for Cabinet
Height: 44.4	case tolerance: $\pm 1.0$		Part number	16-8138
	SIGN	DATE	Customer's code	
DRAWN	Peter	06/06/2008	Drawing number	
CHK'D			Edition number	
APP'D				