

Date: 06/06/2008

NO.:

Customer	Sweden Direktronik	RoHS	Yes
Product Name	Designated Power Distribution Unit for Cabinet	Customer's Code	
Part Number	16-8142	Picture Code	
No.	Item	Detailed Description	
1	Product Series		
2	Socket Type	Double IEC320 C13 Socket[17];	
3	Socket Quantity	34	
4	Power Input	Left end single input	
5	Bracket Install	Inverse installation	
6	Cable with plug	IEC60309 plug (32A 3P+N+E)	
7	Control Function	No controlling function	
8	Protection Function	No protecting function	
9	Case	Black	
10	Cable Specification	5 x 6.0 mm ² x 2M	
11	Product Size	L x W x H = 1122.5 x 68 x 44.4 mm	
12	Mounting Length	1096 mm	
13	Case Length	1069.5 mm	
14	Fittings	2pcs ϕ 6x16mm cross bolt, 2pcs M6 float nut	
15	Product Label	Product Name	Designated Power Distribution Unit for Cabinet
		Specification Model	16-8142
		Rating voltage	380VAC input /250VAC output
		Rating Current	3x32A
		Max. Current	
		Max. Power	
		Safety Authentication	CE
		Logo	RoHS
	Producer		
No.	Add-In		
1	Socket assemble	No	
2	Interior Connection Wire	1.5 mm ²	
3	Interior Connection Style	Group connection	
4	Fix the Cable	Cable clamp	
5	Module Assemble (form left to right)	Please see the following picture	
6	Others	No	
Made by: Peter		Customer confirm:	Check:
			Authorize:

This technology specification is for: design product for customer and confirm customer's requirements, and is also the basic gist for arranging production.

Preview

Date: 06/06/2008



IEC60309 plug (32A 3P+N+E)

DIREKTRONIK

Direktronik AB tel. 08-52 400 700 www.direktronik.se

NO.:

DIMENSION AND TOLERANCES (Unit: mm)			Direktronik AB		
Length:	1122.5	Mounting length:	1096	Customer	Sweden Direktronik
Width:	68	Case length:	1069.5	Product name	Designated Power Distribution Unit for Cabinet
Height:	44.4	case tolerance:	± 1.0	Part number	16-8142
DRAWN	Peter	SIGN	DATE	Customer's code	
CHK'D				Drawing number	
APP'D				Edition number	