







Features

-  10/100BaseT Ethernet port
-  IP68-compliant, -30C to +80C range
-  Free serial-over-IP Tibbo BASIC application available
-  DS1000: Four RS232 ports
-  DS1002: Four RS232/422/485 ports
-  DS1003: Four isolated RS232/422/485 ports



About

The DS1000, DS1002, and DS1003 are 4-port BASIC-programmable industrial controllers designed primarily for serial-over-IP and serial control projects. All three devices come preloaded with a fully functional serial-over-IP application (open-source).

These devices differ in the type of serial ports they offer:

With its four conventional RS232 ports, the DS1000 is ideal for relatively low-cost projects.

For applications requiring a mix of port types, there is the DS1002, which sports universal RS232/422/485 ports with programmable selection of each port's mode.

Finally, especially demanding industrial installations can rely on the DS1003, which adds galvanic isolation on top of the universal ports.

Specifications

- Network side — NB1000 board:
 - Based on the EM1000 BASIC-programmable module;
 - 10/100BaseT, auto-MDIX Ethernet port;
 - 1024KB flash for firmware, application, and data storage;
 - 2KB EEPROM for data storage;
 - RTC with backup supercapacitor;
 - Built-in buzzer;
 - 11 status LEDs;
 - Power: 10-18V;
 - Firmware is upgradeable through the serial port or network.
- Interface side — IB1000, IB1002, or IB1003 board:
 - IB1000 board: four RS232 ports (DS1000);
 - IB1002 board: four RS232/422/485 ports (DS1002);
 - IB1003 board: four isolated RS232/422/485 ports (DS1003);
 - 8 status LED.
 - Dimensions: 91x104x99mm (excluding secondary cover).
 - Extruded-profile aluminum body.
 - IP68 compliant (when used with secondary cover).
 - Operating temperature -30 to +80 degrees C.
 - CE- and FCC-certified.

continued on next page

Specifications (continued)

- Included accessories:
 - DS1000 waterproof kit with secondary cover, cable glands, screws;
 - DMK1000 DIN rail mounting kit;
 - TB1000 terminal block adaptor.
- Optional accessories:
 - 12V/1A adaptor: APR-P0008 (US), APR-P0009 (EU), APR-P0010 (UK);
 - WAS-1499 straight Ethernet cable (for this device can be used as crossover cable too);
 - WAS-P0004(B) DB9M-to-DB9F serial cable (device-to-PC);
 - WAS-P0005(B) DB9F-to-DB9F serial cable (device-to-device).

Programming

Platform Objects

- Sock — socket comms (up to 16 UDP, TCP, and HTTP sessions).
- Net — controls Ethernet port.
- Ser — up to 4 serial ports (UART, Wiegand, and clock/data modes).
- Io — handles I/O lines, ports, and interrupts.
- Lcd — controls graphical display panels (several types supported).
- Rtc — keeps track of date and time.
- Fd — manages flash memory file system and direct sector access.
- Stor — provides access to the EEPROM.
- Romfile — facilitates access to resource files (fixed data).
- Pat — “plays” patterns on up to five LED pairs.
- Beep — generates buzzer patterns.
- Button — monitors MD line (setup button).
- Sys — in charge of general device functionality.

Function Groups: String functions (21 in total!), date/time conversion functions, and hash calculation functions (md5 and sha1).

Variable Types: Byte, char, integer (word), short, dword, long, real, string, plus user-defined arrays and structures.

Tibbo Integrated Development Environment (TIDE)

All BASIC-programmable Tibbo devices are provided with free TIDE software.

Code in Comfort

Enjoy a modern code editor supporting syntax highlighting, context help, code hinting, and auto-completion.

Debug with Ease

Set breakpoints, watch variables, inspect the stack, step through your code... the built-in debugger in Tibbo IDE provides all the tools for fast and convenient debugging.

Our debugger does not rely on any special hardware like an ICE machine or a JTAG board. Simply connect your Tibbo device to the Ethernet, select it in the IDE, and you are all set!

For more information on TIDE, see <http://basic.tibbo.com/product/tide.html>