



Specifications

iSignager LCD Series



Model		iSignager-LCD-10	iSignager-LCD-12	iSignager-LCD-15	iSignager-LCD-15S	iSignager-LCD-17	iSignager-LCD-17S	iSignager-LCD-19	iSignager-LCD-19S	iSignager-LCD-26	iSignager-LCD-42		
LCD	LCD Size	10.4"	12.1"	15"		17"		19"		25.54"	42.02"		
	Max Resolution	800 x 600	1024 x 768	1024 x 768		1280 x 1024		1920 x 1200		1366 x 768			
	Brightness (cd/m ²)	400	450	350		300		350		500			
	Contrast Ratio	500:1	700:1	400:1		800:1		1500:1					
	LCD Color	16.2M	262K	262K		16.7M		16.7M					
	Pixel Pitch (mm)	0.264 (H) x 0.264 (V)	0.240 (H) x 0.240 (V)	0.297 (H) x 0.297 (V)		0.264 (H) x 0.264 (V)		0.294 (H) x 0.294 (V)		0.2865 (H) x 0.2865 (V)	930.25 (H) x 523.01 (V)		
	Viewing Angle (H-V)	120 / 100	160 / 160	120 / 100		160 / 160		176 / 176		178 / 178			
	Backlight MTBF	50000											
	OSD function	N/A		7 KEYS	5 KEYS	7 KEYS	5 KEYS	7 KEYS	5 KEYS	7 KEYS			
	Auto Dimming	N/A		Ambient Light Sensor	N/A	Ambient Light Sensor	N/A	Ambient Light Sensor	N/A	Ambient Light Sensor			
	Second Display	1 x DVI-I (DVI+VGA)		1 x DVI-I (DVI+VGA)	N/A	1 x DVI-I (DVI+VGA)	N/A	1 x DVI-I (DVI+VGA)	N/A	1 x DVI-I (DVI+VGA)			
I/O Interface	Video In/ Audio In	1 x RCA for composite video in 1 x 3.5mm phone jack for audio in											
	USB	1 x USB 2.0											
	Ethernet	1 x 10/100mBase-T											
	Wireless	802.11 b/g wireless		802.11 b/g wireless (for iSignager-LCD-15 & iSignager-LCD-15SWL only)		802.11 b/g wireless (for iSignager-LCD-17 & iSignager-LCD-17SWL only)		802.11 b/g wireless (for iSignager-LCD-19 & iSignager-LCD-19SWL only)		802.11 b/g wireless			
	Serial Port	1 x RS-232											
	Audio out	built-in 1.5W+ 1.5W AMP speaker 1 x 3.5mm audio phone jack				built-in 2W+ 2W AMP speaker 1 x 3.5mm audio phone jack		built-in 3W+ 3W AMP speaker 1 x 3.5mm audio phone jack		built-in 6W+ 6W AMP speaker 1 x 3.5mm audio phone jack		built-in 10W+10W AMP speaker 1 x 3.5mm audio phone jack	
	Remote Control	Panel on/off Volume Control Brightness/ Contrast OSD											
Storage	HDD Drive Bay	2.5" IDE HDD bay											
	SSD Drive Bay	1 x CF Type II slot											
Power	Input Voltage	12VDC in								90V-264V AC in			
	Power adapter	60W ACDC Power Adapter 90VAC~240VAC @50~60Hz input											
	Consumption	27W	27W	27W	41W		42W		128W	213W			
LED Function	1 x Power ON/OFF LED on the front panel												
Operation Temperature	0°C~50°C									0°C~45°C			
Dimension (WxLxD)	276 x 227 x 51 mm	304 x 246 x 50 mm	393 x 308 x 61 mm		428 x 350 x 65 mm		470 x 383 x 67 mm		622 x 425 x 100 mm	1017 x 582 x 135 mm			
Net Weight	1.33 KG	2.12 KG	3.2 KG		3.8 KG		4.4 KG		16.7 kg	42.0 KG			
Front Panel Protection	IP64												
EMC / Safety	CE, FCC, UL												