



IP7133/7134 Home Security Network Camera ***Dual Codec · Dual Streams · 3GPP***

VIVOTEK IP7133 (Wired)/IP7134 (Wireless) is an easy-to-use network camera, specifically designed for home security applications with a compact, stylish exterior. Apart from its ultra-compact size, it is incorporated with a good many advanced features to fit your needs. Embedded with the VIVOTEK VVTK-1000 SoC, it enables simultaneous delivery of dual streams in MPEG-4 and MJPEG with different video resolution and quality upon different devices such as PC or 3G cell phones. With this network camera, you can quickly, easily access it to view the current status of your children, the elderly, or even your pets with live, clear videos while you're away from home. IP7134 also supports built-in 802.11b/g WLAN capability, which can prevent your elegant home decoration from tangled cabling. Additionally, it comes with a push button on the front side for privacy use. You are able to manually stop the operation of video monitoring with ease while getting back home. This considerate design avoids the feeling of being monitored all day long. With the delicate design and versatile functions, VIVOTEK IP7133/IP7134 is definitely the best choice for the fundamental establishment of home security.

Features

- Real-time MPEG-4 and MJPEG Compression (Dual Codec)
- Supports Dual Streams Simultaneously
- 3GPP Mobile Surveillance
- Built-in 802.11b/g WLAN (IP7134)
- Digital I/O for External Sensor and Alarm
- Privacy Button to Pause Monitoring
- Easy to Install with VIVOTEK Installation Wizard 2
- Stylish Design for Home Decoration
- Free-bundled 16-channel Recording Software

System Overview



Specifications

Models

- IP7133
- IP7134 (Wireless)

System

- CPU: VVTK-1000 SoC
- Flash: 4 MB
- RAM: 32 MB
- Embedded OS: Linux 2.4

Lens

- Board lens type, $f = 4.09$ mm, F2.0, Fixed, focus range: 70 cm to infinity

Angle of view

- 49.6° (horizontal)
- 38.2° (vertical)

Shutter Time

- 1/5 sec. to 1/15000 sec.

Image Sensor

- OV 1/4" CMOS sensor in VGA resolution

Minimum Illumination

- 0.4 Lux / F2.0

Video

- Compression: MJPEG & MPEG-4
- Streaming:
 - Simultaneous dual-streaming
 - MPEG-4 streaming over UDP, TCP, or HTTP
 - MPEG-4 multicast streaming
 - MJPEG streaming over HTTP
- Supports 3GPP mobile surveillance
- Frame rates:
 - MPEG-4: Up to 30/25 fps at 640x480
 - MJPEG: Up to 30/25 fps at 640x480

Image Settings

- Adjustable image size, quality, and bit rate
- Time stamp and text caption overlay
- Flip & mirror
- Configurable brightness, contrast, saturation, sharpness, and white balance
- AGC, AWB, AEC (Automatic Exposure Control)
- Supports privacy masks

Audio

- Compression:
 - GSM-AMR speech encoding, bit rate: 4.75 kbps to 12.2 kbps
 - MPEG-4 AAC audio encoding, bit rate: 16 kbps to 128 kbps
- Interface:
 - Built-in microphone
 - Supports audio mute

Networking

- 10/100 Mbps Ethernet, RJ-45
- Protocols: IPv4, TCP/IP, HTTP, UPnP, RTSP/RTP/RTCP, IGMP, SMTP, FTP, DHCP, NTP, DNS, DDNS, and PPPoE
- Built-in 802.11b/g WLAN (IP7134)

Alarm and Event Management

- Triple-window video for motion detection
- One D/I and one D/O for external sensor and alarm
- Event notification using HTTP, SMTP, or FTP
- Local recording of MP4 file

Security

- Multi-level user access with password protection
- IP address filtering
- Wireless: WEP, WPA-PSK, WPA2 (IP7134)

Users

- Camera live viewing for up to 10 clients

Dimension

- 26.9 mm (D) x 86.7 mm (W) x 87.6 mm (H)

Weight

- Net: 106 g (IP7133)
- Net: 122 g (IP7134)

LED Indicator

- System power and status indicator
- System activity and network link indicator
- Privacy button on

Power

- 5V DC
- Power Consumption: Max 5 W (IP7133)
Max 6.6 W (IP7134)

Approvals

- CE, LVD, FCC, VCCI

Operating Environments

- Temperature: 0° ~ 40° C
- Humidity: 20% ~ 80% RH

Viewing System Requirements

- OS: Microsoft Windows 2000/XP/Vista
- Browser: Internet Explorer 6.x or above
- Cellphone: 3GPP player
- Real Player: 10.5 or above
- Quick Time: 6.5 or above

Installation, Management, and Maintenance

- Installation Wizard 2
- 16-CH recording software
- Supports firmware upgrade

Applications

- SDK available for application development and system integration

All specifications are subject to change without notice. Copyright © 2008 VIVOTEK INC. All rights reserved. P/N: 011001900 Ver 1.0