

14-slots Media Converter Rack

Features

- ▶ The configuration of active/standby power supply ensures uninterrupted operation of the system.
- ▶ Provide two power supplies (AC 220V, and DC -48V), enabling the system can work under many operating environments;
- ▶ Supporting simultaneous operation of several module type (module type) media converters at different rates, which greatly improves system adaptability;
- ▶ Supports hot swapping;
- ▶ Application module types: LNK-1100 (10/100M Standalone Media Converter) series and LNK-3011 (10/100/1000M Standalone Media Converter) series



Overview

LNK-R14 is a kind of cost-effective media converter rack (2U) widely used in the equipment room. Different types of module type media converter developed by our company can be inserted into this rack, which total slots up to 14. It is furnished with two power supplies: main power supply and spare one, and supports its automatic switch-over.

Technical Indexes

Parameter	Specifications
Number of slots	14
Structure	2U rack
Dimension	90mm (H) x 485mm (W) x 230mm (D)
Power input	AC Voltage: AC 85~265V; frequency: 50/60 Hz DC voltage: DC -36~72V
Power output	DC5V 16A
Ripple	≤20 mv
Power configuration	Single power supply, or dual power supply for warm backup mode
LED indication	POWER (power supply)
Max power consumption	95W
Operating temperature	-10~55°C
Operating humidity	5%~90%
Maintaining temperature	-40~70°C
Maintaining humidity	5% ~ 90% non-condensing