

Hand-held Inspection Probe



Handheld Inspection are probes of high resolutions. With suitable tips, they could check various ferrules and adapters in FTTH construction and maintenance.

• USB Analysis Inspection Probe



Features:

USB1.0/1.1/2.0 output;
Analysis Software; IEC61300-3-35
Windows; Linux System

• 4-Pin Regular Inspection Probe



Main Configurations

Option1: Probe + 3.5" SD-LCD
Application: Field or Indoor
Advantage: Data saving



Option2: Probe + Mobile phone
Application: Mainly in field
Advantage: Convenience

Tips

| Type | USB Analysis Inspection Probe | 4-Pin Regular Inspection Probe |
|------------------|-------------------------------|--|
| Magnification | 400x or 200x | |
| Resolution Ratio | 0.75 um | |
| Analysis System | Windows/Linux | N/A |
| Display Screen | N/A | 3.5" TFT-LCD, 960x240 pixels |
| Power Supply | 12.6V Li Battery | |
| Weight (kg) | Probe (0.16) | Probe (0.16); Monitor (0.28/0.4); |
| Dimensions (cm) | Probe (11*4*4) | Probe (11*4*4); Monitor (14.5*7.5*4/17*10*4.5) |
| Work/Storage | -20°C~+50°C -30°C~+60°C | |

| Tips Type | Function Description |
|-----------|------------------------------|
| 25-U-M | FC/SC/ST/E2000 UPC connector |
| 125-U-M | LC/MU UPC connector |
| 25-U-F | FC/SC/ST/E2000 UPC bulkhead |
| LC-U-F | LC/MU UPC bulkhead |
| 25-A-M | FC/SC/ST/E2000 APC connector |
| 125-A-M | LC/MU APC connector |
| SC-A-F | SC APC bulkhead |
| FC-A-F | FC APC bulkhead |
| LC-A-F | LC APC bulkhead |

Ordering Information

| Standard Accessories | USB-Analys | 4-Pin Regular |
|---|------------|---------------|
| Probe (200x or 400x) | ■ | ■ |
| 4 Tips (125-U-M/25-U-M/125-U-F/25-U-M) | ■ | ■ |
| 3.5" monitor & 12V AC/DC adapter | □ | ■ |
| Analysis Software & USB Key | ■ | □ |
| Manual & Soft Carrying Bag | ■ | ■ |
| Optional Accessories | | |
| 3.5" SD-monitor; BNC converter; USB converter; Tips | | |