

## PDU Technology Specification

Date: 09/26/2021

NO.: SWDT0312109052

<b>Customer</b>	Direktronik	<b>RoHS</b>	Yes
<b>Product Name</b>	Designated Power Distribution Unit for Cabinet	<b>Customer's Code</b>	<b>116-8405</b>
<b>Part Number</b>	AUE2250D3-06AHCNVB	<b>Picture Code</b>	SWDT0312109052
<b>No.</b>	<b>Item</b>	<b>Detailed Description</b>	
1	Product Series	AUE2250	
2	Socket Type	DIN49440 16A Socket [6];	
3	Socket Quantity	6	
4	Power Input	Left end single input	
5	Bracket Install	Frontal installation	
6	Cable with plug	IEC320 C14 10A plug	
7	Control Function	No controlling function	
8	Protection Function	LED display digital ammeter [1];	
9	Case	Black	
10	Cable Specification	3 x 1.0 mm <sup>2</sup> x 2M	
11	Product Size	L x W x H = 485 x 44.4 x 44.4 mm	
12	Mounting Length	464 mm	
13	Case Length	432 mm	
14	PDU Exponent	0.605	
15	Fittings	2pcs $\phi 6 \times 16$ mm cross bolt, 2pcs M6 float nut,	
16	Product Label	Product Name	Designated Power Distribution Unit for Cabinet
		Specification Model	AUE2250D3-06AHCNVB
		Rating voltage	250VAC 50/60Hz
		Rating Current	10A
		Max. Current	
		Max. Power	2500W
		Safety Authentication	CE
		Logo	RoHS
	Producer		
<b>No.</b>	<b>Add-In</b>		
1	Socket assemble	No	
2	Interior Connection Wire	1.5 mm <sup>2</sup> (16AWG)	
3	Interior Connection Style	Standard connection	
4	Fix the Cable	Cable clamp(11)	
5	Module Assemble ( from left to right )	Pls refer to the drawing	

Preview



IEC320 C14 10A plug

DIMENSION AND TOLERANCES (Unit: mm)			Direktronik		
Length:	485	Mounting length:	464	Customer	Direktronik
Width:	44.4	Case length:	432	Product name	Designated Power Distribution Unit for Cabinet
Height:	44.4	case tolerance:	± 1.0	Part number	116-8405
	SIGN	DATE	Customer's code		
DRAWN	Linda	09/26/2021	Drawing number	SWDT0312109052	
CHK'D			Edition number		
APP'D					