

PDU Technology Specification

Date: 12/27/2022

NO.: SWDT-0312212034

Customer	Direktronik	RoHS	Yes
Product Name	Designated Power Distribution Unit for Cabinet	Customer's Code	
Part Number	20103106	Picture Code	
No.	Item	Detailed Description	
1	Product Series	AUE2250	
2	Socket Type	DIN49440 16A Socket[3];	
3	Socket Quantity	3	
4	Power Input	Left end single input	
5	Bracket Install	Frontal installation	
6	Cable with plug	IEC320 C14 10A plug	
7	Control Function	No controlling function	
8	Protection Function	No protecting function	
9	Case	Black	
10	Cable Specification	3 x 1.0 mm ² x 6M	
11	Product Size	L x W x H = 482 x 44.4 x 44.4 mm	
12	Mounting Length	461 mm	
13	Case Length	429 mm	
14	PDU Exponent	0.431	
15	Fittings	2pcs $\phi 6 \times 16$ mm cross bolt, 2pcs M6 float nut,	
16	Product Label	Product Name	Designated Power Distribution Unit for Cabinet
		Specification Model	20103106
		Rating voltage	250VAC 50/60Hz
		Rating Current	10A
		Max. Current	
		Max. Power	2500W
		Safety Authentication	CE
		Logo	RoHS
	Producer		
No.	Add-In		
1	Socket assemble	No	
2	Interior Connection Wire	1.5 mm ² (16AWG)	
3	Interior Connection Style	Standard connection	
4	Fix the Cable	Cable clamp(11)	
5	Module Assemble (from left to right)	Pls refer to the drawing	

This technology specification is for: design product for customer and confirm customer's requirements, and is also the basic gist for arranging production.

Preview



IEC320 C14 10A plug

DIMENSION AND TOLERANCES (Unit: mm)			Direktronik		
Length:	482	Mounting length:	461	Customer	Direktronik
Width:	44.4	Case length:	429	Product name	Designated Power Distribution Unit for Cabinet
Height:	44.4	case tolerance:	± 1.0	Part number	2 DIREKTRONIK 0103108
	SIGN	DATE	Customer's code		
DRAWN	Linda	12/27/2022	Drawing number	SWDT-0312212034	
CHK'D			Edition number		
APP'D					