

PDU Technology Specification

NO.:

Customer	Direktronik AB.	RoHS	Yes
Product Name	Designated Power Distribution Unit for Cabinet	Customer's Code	
Part Number		Picture Code	
No.	Item	Detailed Description	
1	Product Series		
2	Socket Type	Single IEC320 C13 Socket (Right)[7]; IEC-lock sockets	
3	Socket Quantity	7	
4	Power Input	Left end single input	
5	Bracket Install	Frontal installation	
6	Cable with plug	IEC60309 plug (16A 2P+E)	
7	Control Function	No controlling function	
8	Protection Function	BM PDU_2017 module, integration, LCD Display (left)[1];	
9	Case	Black	
10	Cable Specification	3 x 2.5 mm ² x 2M	
11	Product Size	L x W x H = 488 x 44.4 x 44.4 mm	
12	Mounting Length	467 mm	
13	Case Length	435 mm	
14	PDU Exponent	0.663	
15	Fittings	2pcs φ6×16mm cross bolt, 2pcs M6 float nut,	
16	Product Label	Product Name	Designated Power Distribution Unit for Cabinet
		Specification Model	20101572
		Rating voltage	250VAC 50/60Hz
		Rating Current	16A
		Max. Current	
		Max. Power	4000W
		Safety Authentication	CE
		Logo	RoHS
		Producer	
No.	Add-In		
1	Socket assemble	No	
2	Interior Connection Wire	2.5 mm ² (14AWG)	
3	Interior Connection Style	Standard connection	
4	Fix the Cable	Cable clamp (11)	
5	Module Assemble (from left to right)	Pls refer to the drawing	
6	Others		
Made by:		Customer confirm:	Check: Authorize:

This technology specification is for: design product for customer and confirm customer's requirements, and is also the basic gist for arranging production.

PDU Technology Specification

Date: / /

NO.: SWDT0312004021

Preview



All sockets are IEC-Lock sockets



IEC60309 plug (16A 2P+E)

DIMENSION AND TOLERANCES (Unit: mm)			20101572, Direktronik.se	
Length:	488	Mounting length:	467	Customer
Width:	44.4	Case length:	435	Product name
Height:	44.4	case tolerance:	± 1.0	Designated Power Distribution Unit for Cabinet
	SIGN	DATE	Part number	
DRAWN	Linda		Customer's code	
CHK'D			Drawing number	SWDT0312004021
APP'D			Edition number	