

DATASHEET

YV 2 x 0.5/0.9 white-red, Ring 100 m



General data

Other types on request

Allgemeine Daten

Material outer sheath	-
Armouring	False
Conductor category	Class 1 = solid
Longitudinal water blocking	False
Outdoor use permitted	False
Stranding element	Pairs
Core identification	Colour
Circuit integrity	False
Radial water blocking	False

Kabelaufbau

Diameter conductor	0.5 mm
Stranding	-
Number of stranding elements	2

Kabelmantel

Flame retardant	according to EN 60332-1-2
Protective sheath	False

Umgebungsbedingungen

This datasheet was created automatically on 28-12-2023 . Technical changes reserve

DATASHEET

YV 2 x 0.5/0.9 white-red, Ring 100 m

Permitted cable outer temperature after assembling without vibration	70 - °C
Permitted cable outer temperature during assembling/handling	70 - °C

Elektrische Eigenschaften

Screen over stranding	None
Screen over stranding element	None
Core insulation	PVC

Normen, Zulassungen, Zertifizierungen

Low smoke (according to EN 61034-2)	False
Halogen free (acc. EN 50267-2-2)	False

Available variants

Bezeichnung	Colour outer sheath	Number of cores	Außendurchmesser ca.
YV 2 x 0.5/0.9 white-brown, Ring 100 m	white/brown	2	0,9 mm
YV 2 x 0.5/0.9 red-blue, Ring 100 m	red/blue	2	0,9 mm
YV 2 x 0.5/0.9 white-green, Ring 100 m	white/green	2	0,9 mm
YV 2 x 0.5/0.9 white-yellow, Ring 100 m	white/yellow	2	0,9 mm
YV 2 x 0.5/0.9 white-blue, Ring 100 m	white/blue	2	0,9 mm
YV 2 x 0.5/0.9 white-red, Ring 100 m	white/red	2	0,9 mm
YV 2 x 0.5/0.9 white-black, Ring 100 m	white/black	2	0,9 mm
YV 2 x 0.5/0.9 white-pink, Ring 100 m	white/pink	2	0,9 mm
YV 2 x 0.5/0.9 red-black, Ring 100 m	red/black	2	0,9 mm
YV 2 x 0.5/0.9 red-green, Ring 100 m	red/green	2	0,9 mm