

REV	DATE	DESCRIPTION
B	2013-3-7	增加Type A
C	2016-8-29	增加Type B 铆压反向
D	2018.8.25	螺丝变更
E	2023.8.21	螺丝变更

Material & finish
SHELL:
steel
Zinc plated, Tin plated
or Nickel plated steel
PIN CONTACT:
Phosphor bronze or brass
Gold Plated
INSULATOR:
PBT & Glass-fibre reinforced
UL-94-V0
CURRENT RATING: 5Amp
DIELECTRIC STRENGTH:
1000V for one minute
INSULATOR RESISTANCE:
1000MΩ MIN.(at 500V DC)
CONTACT RESISTANCE: 25mΩ Max. mated
TEMPERATURE:
-55°C to +105°C

57RI 50 P * * A 0 036-1

FILE NO:001-1000
CONTACT LENGTH:0.00M
0-N/A
SHELL:
A: NICKEL PLATED
CONTACT PLATING:
A: GOLD FLASH B: 3U" C: 5U"
D: 10U" E: 15U" F: 20U"
INSULATOR COLOR:
B-BLUE K-BLACK
CONTACT TYPE:
P-PLUG
NO. OF CONTACTS:
50

UNIT : mm

DIREKTRONIK

MODEL NAME:

RJ21 50 pin
angled

SELECT	1	2	3	EXTRA
DIM	1	2	3	
0.000	0.05	0.05	0.10	
0.00	0.10	0.15	0.20	
0.0	0.15	0.25	0.30	
0.	0.25	0.30	0.40	
ANGLE	1.0°	3.0°	5.0°	

PART NO: 20123961

APPROVED BY:

FILE NO.FUY57036-1

CHECKED BY:

SCALE: 1 : 1

DRAW BY: 韦锋

DATE :