



MATERIAL
 Housing: Polycarbonate resin high-impact UL94V-0 thermoplastic
 Gasket: Rubber
 RoHS 2 compliant

PHYSICAL CHARACTERISTICS
 Operating temperature range: -10°C to 60°C
 Storage temperature range: -40°C to 68°C
 Humidity: 10%-90%RH

ENCLOSURE
 1. Screw X 4 pcs
 2. Screw Cap X 4 PCS

IP67
 According to IEC 60529:2001-02
 Degrees of protection provided by enclosures
 6: Dust-tight
 7: Protected from immersion in water for 30 minutes at a depth of 1 meter

NOTE
 1. Knockout holes x 2
 2. Suitable for standard M32 conduit gland
 3. Suitable for standard M16 cable gland x 2

DRAWN BY Kihai Lee		HSIING CHAU INDUSTRIAL CO., LTD.	
APPROVED BY Kevin Wu			
UNIT: mm [inch]		PART NO.	VER.
TOLERANCES:		IEMB2XX 1	
-20	-50	-150	150-
±0.2	±0.4	±0.5	±1.5
ANGLE		CUSTOMER P/N.	
		DATE	SHEET
3rd Angle Projection		2018.01.22	1/1

REV.	DESCRIPTION	DATE