MerryloT Motion Detection

Doc ver.: BQW_03_0036.006





🙎 Features

- Compliance to LoRaWAN1.0.3
- Dual Passive Infrared detectors and Fresnel Lens
- IP40 equivalent
- Battery-powered (2 standard AA alkaline batteries)
- Built-in alarm buzzer with sound pressure level 80 dB(min)
- Be notified of possible abnormal movement
- Support both desk and room occupancy
- Power on-and-play installation
- Support coverage test by pressing test button



Dataprodukter utöver det vanliga

The MerryloT Motion Detection utilized with LoRaWAN 1.0.3 connectivity, allows to sense and measure movement. Applications such as homes or buildings security, facility management systems, occupancy of the desks, conference rooms, bathrooms, etc.

Specification			
Model Name	MS10		
Frequency	EU 868 MHz US 902~928 MHz		
Antenna Gain	-2dBi Peak		
RF Sensitivity	-135dBm		
Battery Type	1.5 V AA Alkaline x 2 pcs, 5400 mAh (75ΩCont. discharge)		
Battery Lifetime*	About 3 years. *Note: Battery life is mainly determined by the reporting frequency. Other factors include moisture and high temperature.		
Average Current	135 mA maximum / 100 uA minimum		
Protocol	LoRaWAN 1.0.3		
Operation Temperature	0 to 50°C		
Environmental Rating	IP40 equivalent		
Dimensions	70 mm x 25 mm x 70 mm		
Weight	91 g		
Sensor	 Dual Passive Infrared detector with Fresnel Lens Detection angle: 123°H x 93°V Detection range: 7 meters Temperature sensor: Accuracy: ± (1°C) Humidity sensor: Accuracy: ± 5 % Three-axis linear accelerometer 		
Type Approval	CE/FCC/IC approved.		



MerryloT Motion Detection

Doc ver.: BQW_03_0036.006

SKU Detail			
SKU	Country	Frequency Band (MHz)	
MS10-915	USA	US915 (902~928)	
MS10-868	Europe	EU868 (862~870)	

