MerryloT Leak Detection



Seatures

- Compliance to LoRaWAN1.0.3
- Built-in water-sensing probes
- IP67-rated waterproof housing
- Battery-powered (2 standard AA alkaline batteries)
- Detection for both flood and water dripping
- Built-in alarm buzzer with sound pressure level 80 dB(min)
- Press-and-play installation
- · Support coverage test by pressing test button



Dataprodukter utöver det vanliga

The **MerryIoT Leak Detection** utilizes LoRaWAN connectivity to sends uplink notification when water dripping, or flood is detected. And with the built-in alarm buzzer, you wouldn't miss the possible flooding.

Specification		
Model Name	WL10	
Frequency	EU 868 MHz US 902~928 MHz	
Antenna Gain	-2dBi Peak	
RF Sensitivity	-135dBm	
Battery Type	1.5 V AA Alkaline x 2 pcs, 5400 mAh (75ΩCont. discharge)	
Battery Lifetime*	About 3 years. *Note: Battery life is mainly determined by the reporting frequency. Other factors include moisture and high temperature.	
Average Current	135 mA maximum / 100 uA minimum	
Protocol	LoRaWAN 1.0.3	
Operation Temperature	0 to 50°C	
Environmental Rating	IP67 equivalent	
Dimensions	70 mm x 26.5 mm x 70 mm	
Weight	89 g	
Sensor	 Water sensing probes Temperature sensor: Accuracy: ± (1°C) Humidity sensor: Accuracy: ± 5 % Three-axis linear accelerometer 	
Type Approval	CE/FCC/IC approved.	



MerryloT Leak Detection

SKU Detail			
SKU	Country	Frequency Band (MHz)	
WL10-915	USA	US915 (902~928)	
WL10-868	Europe	EU868 (862~870)	

2021 © Browan Communications Inc., All Rights Reserved. This document is for planning purposes only, and is not intended to modify or supplement any specifications or warranties relating to products of Browan Communications. Browan may make changes to specifications and descriptions at any time, without notice.

