

DIREKTRONIK

Dataprodukter utöver det vanliga

Best.nr: 20101517



RECORD, STREAM AND
VIDEOCONFERENCE
WITH RADA BRIDGE

HDMI to USB BRIDGE

QUICK INSTALLATION GUIDE

CONNECTION DIAGRAM



1. OUTPUT - Connect to a display with HDMI cable.
2. INPUT - Connect a video source with HDMI cable.
3. USB 3.0 - Connect to a computer with USB 3.0 cable.
4. MIC IN: Connect a microphone (overwrites HDMI sound).
5. HEADSET IN/OUT - Connect a headset for voice over and playback (does not overwrite HDMI sound)
6. BLUE LED - Stays on when HDMI input is connected.
7. RED LED - Power and status. LED stays on when device has power, flashes when working.

How to select your HDMI-USB Bridge in various applications:

Skype

- Step 1. Connect the BRIDGE to your computer via USB.
- Step 2. Open Skype, click on "Settings", and proceed to "Audio & Video".
- Step 3. Select "Camera" to be "RADA Bridge".
- Step 4. Select "Microphone" to be "Digital Audio Interface (RADA Bridge)**".
- Step 5. Now connect the device you want to convert to the Bridge.
Done!

Hangouts

- Step 1. Connect the BRIDGE to your computer via USB.
- Step 2. Open Hangouts, click on "Settings".
- Step 3. In "Devices" Tab, select "Camera" to be "RADA Bridge".
- Step 4. Select "Microphone" to be "Digital Audio Interface (RADA Bridge)".
- Step 5. Now connect the device you want to convert to the BRIDGE.
Done!

OBS

- Step 1. Connect the BRIDGE to your computer via USB.
- Step 2. Open OBS, under "Sources", press on "+".
- Step 3. Select "Video Capture Device".
- Step 4. Select "Create New" and press "Ok".
- Step 5. In "Device" tab, select "RADA Bridge".
- Step 6. Select "Audio Input Capture", in Device Tab, select "Digital Audio Interface (RADA Bridge)".
- Step 7. Now connect the device you want to convert to the BRIDGE.
Done!

HDMI to USB BRIDGE can be used in the same way in many other applications. Just select it as your camera and enjoy!

* Select BRIDGE as a microphone only if you want to transfer HDMI audio or add voice over. You can connect a headset (audio in/out) to the headset jack to add an extra audio layer and to hear playback. You can connect a microphone to the mic jack to overwrite HDMI sound with mic audio. Both jacks can be used at the same time. Microphone in the mic jack will have lower sound when used with the headset jack.

PACKAGE CONTENT

A-BR01 - HDMI to USB BRIDGE

USB 3.0 Type A cable

AUX cable

USB Type A to USB Type C adapter

Quick Installation Guide

SPECIFICATION

Model Name	20101517
Video	HDMI In x 1, HDMI Out x 1(loop-through), USB 3.0* Out x 1 *Also compatible with USB 2.0
Audio	3.5mm Mic In x 1 (TRRS cable) 3.5mm Headset In/Out (TRRS CTIA or OMTP) x 1
Video Quality	1920 x 1080 60 fps, also supports lower resolutions
Power Supply	5V, 1A via USB
Compatibility	Windows (7 and above), Linux (2.6.38 Kernel and above), Mac OS (10.8 and above)
Working Temperature	0°C to 40°C (32°F to 104°F)
Dimensions	117 x 72 x 15.5 mm
Weight	168 g

The logo for DIREKTRONIK features the brand name in a bold, italicized, sans-serif font. The letters are white with a thick red outline, set against a yellow background that curves upwards from the bottom of the page.