PX Environmental Sensor Specifications



DPX-T1Temperature sensor x1 RJ-12 connector 1-Wire Interface Operating Range -40°C to +85°C Accuracy ±2°C



DPX-T2H2

Length 3m

Temperature sensor x2 Humidity sensor x2 RJ-12 connector 1-Wire Interface Temp Operating Range -40°C to +85°C Temp Accuracy ±2°C Humidity Accuracy ±3.5%RH at 25°C Length 6m total, T1/H1 sensors 3m apart



Know more. Manage smarter.



DPX-T1H1

Temperature sensor x1
Humidity sensor x1
RJ-12 connector
1-Wire Interface
Temp Operating Range -40°C to +85°C
Temp Accuracy ±2°C
Humidity Accuracy ±3.5%RH at 25°C
Length 3m



DPX-ENVHUB4

RJ-12 connector for input x1
RJ-12 connector for output x4
RJ-12 to RJ-12 cable included for input to PX rack PDU
LED status indicator
Dimensions (WxDxH):
4.21" x 1.5" x 0.71"
107 x 37 x 18 mm
Color: Black powder coat

Mounting: Rack mount bracket included

©2009 Raritan Inc. All rights reserved. Raritan®, Know more. Manage smarter.™, CommandCenter®, Dominion®, Power IQ™ and Paragon® are registered trademarks of Raritan Inc. or its wholly-owned subsidiaries. All other marks are registered trademarks or trademarks of their respective owners.

Raritan is a leading provider of secure IT infrastructure management solutions that provide IT directors, managers and administrators the control they need to optimize data center productivity, enhance branch office operations and increase overall power management efficiency. In over 50,000 locations around the world, our integrated secure in-band and out-of-band server access, control and power management products help companies better monitor and manage server access, utilization and energy consumption. Raritan's OEM division provides advanced embedded hardware and firmware for server and client management, including KVM over IP, IPMI, intelligent power management and other industry standards-based management applications. Based in Somerset, NJ, Raritan has 38 offices worldwide, serving 76 countries. For more information, please visit Raritan.com